



H0-H0

C1 C2 C3

A B C D

85.000

L2T

L2
PL. 5

L1T

L1
PL. 5

85.000

90.400

Road

93.600

C2
PL. 8

C3
PL. 8

C1
PL. 6.7

85.000

Erector's note:
Normal erection operations include the correction of minor misfits by moderate amounts of straightening, shimming, reaming, chipping, cutting or grinding and the drawing of elements into line through the use of split pins. Misfits which cannot be corrected by the foregoing means or which require major changes in equipment configuration are to be reported immediately to the supplier by the erector, to enable the supplier either to correct the misfit or to approve the most efficient and economic method of correction to be implemented.

This drawing to be read in conjunction with instruction No. 781500.
For equipment with reference Nos. with the loads are only specified on outline and load drawings.
In the calculation of natural loads it is assumed, that expansion joints on machines and ducts, do not transfer forces.

Scale:	Drawn:	Appr.:	Appr. Date:	Zone/Desc.:
1:200	CM	SB		Reference No. with see legend No. 30095693

2500 TPD
212 Pozzolana intake and crusher

General Arrangement Drawing Plan No. 2

The information transmitted by this document is the proprietary and confidential property of and may not be duplicated, disclosed, or utilized without written consent from

No.: 13300415 Verz: 1.0